

Tutorial on Apache

[apache-mc.org]

igor@konnov.phd

TLA⁺ Community Meeting 2024

Milan, Sep 10, 2024



“constant blasting”

v0.15 typechecker Snowcat

quint-lang.org

v0.5.1 @ OOPSLA19

v0.3.0
TLA+ CM 2018

prototypes

theory

**transition
splitting**
@ ABZ18

Model checking
Tendermint consensus
& light client [+inductive]

**model-based
testing**

idea of Quint

security audits

**randomized
symb. exec.**

liveness to
safety

- type checker
- **randomized
execution**
- REPL

arrays encoding
@ TACAS23

2016

2017

2018

2019

2020

2021

2022

2023

2024

informal
SYSTEMS



Inria

vienna
business
agency

2024: independent researchers



Jure Kukovec



Igor Konnov
@konnov



Thomas Pani




Andrey Kuprianov

[protocols-made-fun.com]



code4rena




**Stellar
Community
Fund**



**ethereum
foundation**



**Matter
Labs**



[github.com/apalache-mc/apalache]



APALACHE

A symbolic model checker for TLA+

build passing

Apalache translates [TLA+](#) into the logic supported by SMT solvers such as [M](#) inductive invariants (for fixed or bounded parameters) and check safety of b... (checking). To see the list of supported TLA+ constructs, check the [supporte](#) under the same assumptions as [TLC](#). However, Apalache benefits from cons... potentially larger state-spaces, e.g., involving integer clocks and Byzantine f...

To learn more about TLA+, visit [Leslie Lamport's page on TLA+](#) and his [Vide](#)

Releases

Check the [releases page](#) for our latest release.

For a stable release, we recommend that you pull the latest docker image with `docker pull ghcr.io/apalache-mc/apalache:main`, use the jar from the most recent release, or checkout the source code from the most recent release tag.


To try the latest cool features, check out the head of the [main branch](#).

[apalache.discourse.group]

categories ▾ tags ▾ Latest Hot Categories

Topic	Replies	Activity
🚩 Welcome to Apalache: symbolic model checker for TLA+ and Quint! 🤗 ■ General We are so glad you joined us. Apalache: symbolic model checker for TLA+ and Quint The place to ask questions and discuss applications and research Here are some things you can do to get started: 🗣️ Intr... read more	0	1d
Example: trying to run `apalache-mc check` on `CoffeeCan.tla` ■ Apalache Questions	1	23h

Constant blasting



Translation to SMT

APALACHE: model checker for TLA⁺

- a symbolic model checker
- parameterized verification



Jure Kukovec



Thanh-Hai Tran



Marijana Lazić



Josef Widder

TLA⁺ Model Checking Made Symbolic [OOPSLA'19]

Mimic the semantics implemented by TLC – explicit model checker

Compute **layout of data structures**, constrain **contents with SMT**

Define operational semantics via reduction rules – **for bounded data structures**

Trade efficiency for expressivity

Trivial example

```
1 ----- MODULE t -----  
2 EXTENDS Integers  
3 VARIABLE  
4   \* @type: Int;  
5   x  
6 Init  $\triangleq x \in 0..2$   
7 Next  $\triangleq x' = x - 1$   
8 Inv  $\triangleq x \geq 0$   
9 =====
```

→ apalache-examples git:(main) x █

```
$ apache-mc check --write-intermediate=true --debug --inv=Inv t.tla
```

```
...
```

```
PASS #13: BoundedChecker
```

```
State 0: Checking 1 state invariants
```

```
State 0: state invariant 0 holds.
```

```
Step 0: picking a transition out of 1 transition(s)
```

```
State 1: Checking 1 state invariants
```

```
State 1: state invariant 0 violated.
```

```
1  ----- MODULE t -----  
2  EXTENDS Integers  
3  VARIABLE  
4    \* @type: Int;  
5    x  
6  Init  $\triangleq$   $x \in 0..2$   
7  Next  $\triangleq$   $x' = x - 1$   
8  Inv  $\triangleq$   $x \geq 0$   
9  =====
```

```


7 ;; declare cell($C$0): CellTFrom(Bool)
8 (declare-const $C$0 Bool)
9 (assert (= $C$0 false))
10 ;; declare cell($C$1): CellTFrom(Bool)
11 (declare-const $C$1 Bool)
12 (assert (= $C$1 true))
13 ;; declare cell($C$2): CellTFrom(Set(Bool))
14 (declare-sort Cell_Sb 0)
15 (declare-const $C$2 Cell_Sb)
16 ;; declare cell($C$3): InfSet[CellTFrom(Int)]
17 (declare-sort Cell_Zi 0)
18 (declare-const $C$3 Cell_Zi)
19 ;; declare cell($C$4): InfSet[CellTFrom(Int)]
20 (declare-const $C$4 Cell_Zi)
21 ;; assert ~$C$0
22 (assert (not false))
23 ;; assert $C$1
24 (assert true)
25 ;; declare edge predicate in_b0_Sb2: Bool
26 (declare-const in_b0_Sb2 Bool)
27 ;; declare edge predicate in_b1_Sb2: Bool
28 (declare-const in_b1_Sb2 Bool)
29 ;; assert Apalache!StoreInSet($C$0, $C$2)
30 (assert in_b0_Sb2)
31 ;; assert Apalache!StoreInSet($C$1, $C$2)
32 (assert in_b1_Sb2)

```


```

35 ; ----- STEP: 0, SMT LEVEL: 2 TRANSITION: 0 {
36 ; QuantRule(Apalache!Skolem( $\exists t\_1\$1 \in (0 .. 2)$ ): (Apalache!==(x
37 ; skolemizable existential t_1$1 over 0..2
38 ;; declare cell($C$5): CellTFrom(Int)
39 (declare-const $C$5 Int)
40 ; IntCmpRule($C$5  $\geq$  0) {
41 ;; declare cell($C$6): CellTFrom(Bool)
42 (declare-const $C$6 Bool)
43 ;; assert $C$6 = ($C$5  $\geq$  0)
44 (assert (= $C$6 ( $\geq$  $C$5 0)))
45 ; } IntCmpRule returns $C$6 [7 arena cells]
46 ;; assert $C$6
47 (assert $C$6)
48 ; IntCmpRule($C$5  $\leq$  2) {
49 ;; declare cell($C$7): CellTFrom(Bool)
50 (declare-const $C$7 Bool)
51 ;; assert $C$7 = ($C$5  $\leq$  2)
52 (assert (= $C$7 ( $\leq$  $C$5 2)))
53 ; } IntCmpRule returns $C$7 [8 arena cells]
54 ;; assert $C$7
55 (assert $C$7)
56 ; AssignmentRule(Apalache!==(x', t_1$1)) {
57 ; SubstRule(t_1$1) {
58 ; } SubstRule returns $C$5 [8 arena cells]
59 ; } AssignmentRule returns $C$1 [8 arena cells]
60 ; } QuantRule returns $C$1 [8 arena cells]
61 (push) ;; becomes 3
62 ;; assert $C$1
63 (assert true)
64 (check-sat)
65 ;; sat = SATISFIABLE

```



```
67 ; IntCmpRule(x < 0) {
68 ;; declare cell($C$8): CellTFrom(Bool)
69 (declare-const $C$8 Bool)
70 ;; assert $C$8 = ($C$5 < 0)
71 (assert (= $C$8 (< $C$5 0)))
72 ; } IntCmpRule returns $C$8 [9 arena cells]
73 ;; assert $C$8
74 (assert $C$8)
75 (check-sat)
76 ;; sat = UNSATISFIABLE
```




```
91 ; ----- STEP: 1, SMT LEVEL: 3 TRANSITION: 0 {
92 ; AssignmentRule(Apalache! := (x', x - 1)) {
93 ; IntArithRule(x - 1) {
94 ;; declare cell($C$10): CellTFrom(Int)
95 (declare-const $C$10 Int)
96 ;; assert $C$10 = ($C$5 - 1)
97 (assert (= $C$10 (- $C$5 1)))
98 ; } IntArithRule returns $C$10 [11 arena cells]
99 ; } AssignmentRule returns $C$1 [11 arena cells]
100 (push) ;; becomes 4
101 ;; assert $C$1
102 (assert true)
103 (check-sat)
104 ;; sat = SATISFIABLE
105 (push) ;; becomes 5
106 ; IntCmpRule(x < 0) {
107 ;; declare cell($C$11): CellTFrom(Bool)
108 (declare-const $C$11 Bool)
109 ;; assert $C$11 = ($C$10 < 0)
110 (assert (= $C$11 (< $C$10 0)))
111 ; } IntCmpRule returns $C$11 [12 arena cells]
112 ;; assert $C$11
113 (assert $C$11)
114 (check-sat)
115 ;; sat = SATISFIABLE
```



Static picture of TLA⁺ values and relations between them

Arena:



SMT:

integer

sort Int

Boolean

sort Bool


name, e.g., "abc", uninterpreted sort

finite set:

- a constant c of uninterpreted sort set_{τ}
- propositional constants for members

$in_{\langle c_1, c \rangle}, \dots, in_{\langle c_n, c \rangle}$

Arenas for sets: $\{\{1, 2\}, \{2, 3\}\}$



SMT defines the contents, e.g., to get $\{\{1\}, \{2\}\}$:

$$in_{\langle c_1, c_4 \rangle} \wedge \neg in_{\langle c_2, c_4 \rangle} \wedge in_{\langle c_2, c_5 \rangle} \wedge \neg in_{\langle c_3, c_5 \rangle}$$


Arenas

- Directed acyclic graphs
- Nodes represent symbolic values of TLA⁺ expressions
- Edges represent **potential membership**

Rewriting the set construction

$\{1, 2\} \rightsquigarrow \{c_1, 2\} \rightsquigarrow \{c_1, c_2\} \rightsquigarrow c_3$

Corresponding arena




Rewriting and arenas

Rewriting the set filtering

$$\{x \in \{1, 2\} : p(x)\} \rightsquigarrow \{x \in c_3 : p(x)\} \rightsquigarrow c_4$$

Corresponding arena



SMT constraints

Generated constraints

$$en\langle c_4, 1, c_1 \rangle \Leftrightarrow en\langle c_3, 1, c_1 \rangle \wedge c_5 = \text{true}$$

$$en\langle c_4, 2, c_2 \rangle \Leftrightarrow en\langle c_3, 2, c_2 \rangle \wedge c_6 = \text{true}$$


Set filtering

$$\{x \in \{1, 2\} : p(x)\}$$

$$p(1) \rightsquigarrow c_5 : \text{Bool}$$

$c_3 : \text{Set}[\text{Int}]$ $c_4 : \text{Set}[\text{Int}]$


$$p(2) \rightsquigarrow c_6 : \text{Bool}$$



Arena	SMT encoding
Node	Uninterpreted constant
Edge	Unique Boolean constant

Nested sets

Nested sets
 $\{ \{1, 2\}, \{2, 3\} \}$



SMT constraints

$$\begin{aligned} &en\langle c_6, 1, c_4 \rangle \wedge en\langle c_6, 1, c_5 \rangle \\ &\wedge en\langle c_5, 1, c_2 \rangle \wedge en\langle c_5, 2, c_3 \rangle \\ &\wedge en\langle c_4, 1, c_1 \rangle \wedge en\langle c_4, 1, c_2 \rangle \\ &\wedge c_1 = 1 \wedge c_2 = 2 \wedge c_3 = 3 \end{aligned}$$

[8009 arena cells] vs. [6009 arena cells]

----- MODULE t2 -----

EXTENDS Integers

VARIABLE

```
\* @type: Set(Int);  
S
```

```
Init ≜  
S = {}
```

```
Next ≜  
∃ i ∈ ℤ:  
  ∧ 0 ≤ i ∧ i ≤ 5  
  ∧ S' = S ∪ { i }
```

```
Inv ≜  
2000 ∉ S
```

=====

```
$ hyperfine "apalache-mc check  
--length=1000 --inv=Inv t2.tla"
```

```
...  
Time (mean ± σ): 120.660 s ± 0.690 s
```

```
$ hyperfine "apalache-mc check  
--length=1000 --inv=Inv t3.tla"
```

```
...  
Time (mean ± σ): 129.939 s ± 4.982 s
```

----- MODULE t3 -----

EXTENDS Integers

VARIABLE

```
\* @type: Set(Int);  
S
```

```
Init ≜  
S = {}
```

```
Next ≜  
∃ i ∈ 0..5:  
  S' = S ∪ { i }
```

```
Inv ≜  
2000 ∉ S
```


=====

Encoding with SMT arrays

- Using SMT arrays for TLA⁺ sets and functions: QF_AUFNIA
- [Rodrigo Otoni](#), IK, J. Kukovec, P. Eugster, N. Sharygina
- Working faster on classical fault-tolerant algorithms

Symbolic Model Checking for TLA+ Made Faster [TACAS'23]

Exploration techniques



Bounded model checking

Input: *Init*, *Next* and *Inv*

0. $\text{Init} \wedge \neg \text{Inv}'$
1. $(\text{Init} \cdot \text{Next}) \wedge \neg \text{Inv}'$
2. $(\text{Init} \cdot \text{Next} \cdot \text{Next}) \wedge \neg \text{Inv}'$
- ...
- k. $(\text{Init} \cdot \text{Next} \cdot \dots \cdot \text{Next}) \wedge \neg \text{Inv}'$


Backend:



SMT
(Microsoft z3)

k is the bound

Example: 2D labyrinth



```
9  CONSTANT
10  \* The maximal x-coordinate.
11  \* @type: Int;
12  MAX_X,
13  \* The maximal y-coordinate.
14  \* @type: Int;
15  MAX_Y,
16  \* The set of walls.
17  \* @type: Set(<<Int, Int>>);
18  WALLS,
19  \* The goal coordinates.
20  \* @type: <<Int, Int>>;
21  GOAL
22
23  VARIABLES
24  \* @type: Int;
25  x,
26  \* @type: Int;
27  y
28
29  Init  $\triangleq x = 0 \wedge y = 0$ 
```

```
31  Left  $\triangleq$ 
32   $\exists d \in 1 .. MAX\_X:$ 
33   $\wedge x - d \geq 0 \wedge x' = x - d$ 
34   $\wedge \forall i \in 1..MAX\_X:$ 
35   $\quad (i \leq d) \Rightarrow (x - i, y) \notin WALLS$ 
36   $\wedge UNCHANGED y$ 
```


```
52  Down  $\triangleq$ 
53   $\exists d \in 1 .. MAX\_Y:$ 
54   $\wedge y + d \leq MAX\_Y \wedge y' = y + d$ 
55   $\wedge \forall j \in 1..MAX\_Y:$ 
56   $\quad (j \leq d) \Rightarrow (x, y + j) \notin WALLS$ 
57   $\wedge UNCHANGED x$ 
58
59  Next  $\triangleq$  Left  Right  Up  Down
```

```
61  \* Check this invariant to find a path to the goal:
62  \* apalache-mc check --length=20 --inv=GoalInv MC_labyrinth_10x10.tla
63  GoalInv  $\triangleq (x, y) \neq GOAL$ 
64
65  \* Check this invariant to make sure that we do not walk through walls:
66  \* apalache-mc check --length=20 --inv=NoWallInv MC_labyrinth_10x10.tla
67  NoWallInv  $\triangleq (x, y) \notin WALLS$ 
```


Model checking instance

```
1  ----- MODULE MC_labyrinth_10x10 -----
2  MAX_X  $\triangleq$  9
3  MAX_Y  $\triangleq$  9
4  \* @type: <<Int, Int>>;
5  GOAL  $\triangleq$  (9, 9)
6  \* @type: Set(<<Int, Int>>);
7  WALLS  $\triangleq$  {
8      (0, 1), (2, 0), (2, 1),
9      (4, 1), (4, 2), (5, 2),
10     (0, 3), (1, 3), (2, 3),
11     (4, 4), (5, 4), (1, 5),
12     (7, 1), (7, 2), (7, 3),
13     (7, 5), (8, 5), (9, 5),
14     (3, 6), (5, 6),
15     (1, 7), (2, 7), (3, 7),
16     (4, 7), (5, 7), (6, 7),
17     (7, 7), (8, 7), (9, 7),
18     (2, 8), (6, 8), (8, 8),
19     (0, 9), (4, 9)
20 }
```

```
22  \ VARIABLES
23      \* @type: Int;
24      x,
25      \* @type: Int;
26      y
27
28  INSTANCE labyrinth
29  =====
```



Bounded model checking


```
$ apalache-mc check --length=30 --inv=GoalInv MC_labyrinth_10x10.tla
```

```
PASS #13: BoundedChecker
State 0: Checking 1 state invariants
State 0: state invariant 0 holds.
Step 0: picking a transition out of 1 transition(s)
Step 1: Transition #0 is disabled
State 1: Checking 1 state invariants
State 1: state invariant 0 holds.
Step 1: Transition #2 is disabled
Step 1: Transition #3 is disabled
Step 1: picking a transition out of 1 transition(s)
State 2: Checking 1 state invariants
State 2: state invariant 0 holds.
Step 2: Transition #1 is disabled
Step 2: Transition #2 is disabled
State 2: Checking 1 state invariants
State 2: state invariant 0 holds.
Step 2: picking a transition out of 2 transition(s)
State 3: Checking 1 state invariants
State 3: state invariant 0 holds.
State 3: Checking 1 state invariants
State 3: state invariant 0 holds.
Step 3: picking a transition out of 4 transition(s)
```


```
Step 12: picking a transition out of 4 transition(s)
State 13: Checking 1 state invariants
State 13: state invariant 0 holds.
State 13: Checking 1 state invariants
Check the trace in: /Users/igor/devl/apalache-examples/1
06-25_17911346319537945941/violation1.tla, /Users/igor/c
0x10.tla/2024-09-06T09-06-25_17911346319537945941/MCvio
alache-out/MC_labyrinth_10x10.tla/2024-09-06T09-06-25_17
e-examples/labyrinth/_apalache-out/MC_labyrinth_10x10.t
on I@09:07:05.152
State 13: state invariant 0 violated.
Found 1 error(s)
The outcome is: Error
Checker has found an error
It took me 0 days 0 hours 0 min 39 sec
Total time: 39.830 sec
```

```
Benchmark 1: ~/devl/apalache/bin/apalache-mc check --length=30 --inv=GoalInv MC_labyrinth_10x10.tla
Time (mean ± σ): 30.723 s ± 1.948 s [User: 34.087 s, System: 0.418 s]
Range (min ... max): 26.730 s ... 33.271 s 10 runs
```

Why slow down?



Randomized symbolic execution



[bounded model checking]

```
$ hyperfine -i -r 100 "apache-mc check --length=30 --inv=GoalInv MC_labyrinth_10x10.tla"
```

```
Time (mean ± σ):      35.575 s ± 5.655 s    [User: 38.293 s, System: 0.623 s]  
Range (min ... max):  25.423 s ... 52.707 s    100 runs
```

[randomized symbolic execution]

```
$ hyperfine -i -r 100 "apache-mc simulate --length=50 --inv=GoalInv MC_labyrinth_10x10.tla"
```

```
Time (mean ± σ):      134.850 s ± 112.288 s   [User: 134.858 s, System: 3.582 s]  
Range (min ... max):  5.845 s ... 406.693 s   100 runs
```

Randomized symbolic execution in parallel

```
$ seq 0 30 | parallel --delay 1 --halt now,fail=1  
  apalache-mc simulate --out-dir=s/{} \  
  --length=50 --inv=GoalInv MC_labyrinth_10x10.tla
```

```
-----  
Symbolic runs left: 99
```

```
State 38: state invariant 0 violated. ✘
```

```
Total time: 17.457 sec
```

```
$ hyperfine -i “[...above...]”
```

```
Time (mean ± σ):   40.474 s ± 21.095 s   [User: 31.413 s, System: 1.407 s]  
Range (min ... max):  9.508 s ... 79.283 s   10 runs
```


Recall the figures for “check”:

```
Time (mean ± σ):   35.575 s ±  5.655 s   [User: 38.293 s, System: 0.623 s]  
Range (min ... max): 25.423 s ... 52.707 s   100 runs
```



32 cores, 128G RAM

Unbounded executions?



Inductive invariants

```
61  \* Check this invariant to find a path to the goal:
62  \* apalache-mc check --length=20 --inv=GoalInv MC_labyrinth_10x10.tla
63  \ GoalInv  $\triangleq$   $\langle x, y \rangle \neq \text{GOAL}$ 
64
65  \* Check this invariant to make sure that we do not walk through walls:
66  \* apalache-mc check --length=20 --inv=NoWallInv MC_labyrinth_10x10.tla
67  \ NoWallInv  $\triangleq$   $\langle x, y \rangle \notin \text{WALLS}$ 
68
69  \* A few definitions to check NoWallInv for arbitrary long executions.
70
71  \ TypeOK  $\triangleq$ 
72  |    $\wedge x \in 0..MAX\_X$ 
73  |    $\wedge y \in 0..MAX\_Y$ 
74
75  \* 1. apalache-mc check --length=0 --init=IndInv --inv=NoWallInv MC_labyrinth_10x10.tla
76  \* 2. apalache-mc check --length=0 --init=Init --inv=IndInv MC_labyrinth_10x10.tla
77  \* 3. apalache-mc check --length=1 --init=IndInv --inv=IndInv MC_labyrinth_10x10.tla
78  \ IndInv  $\triangleq$  TypeOK  $\wedge$  NoWallInv
```


Gotchas with inductive invariants

- Apache still needs bounded data structures in `Init`
- Unbounded integers are OK, but only a bounded number of them
- Disproving `TypeOK` is often too hard
- Apache-specific hack: `Gen(k)` produces data structures of width $\leq k$

TypeOK that is “too much”

TypeOK \triangleq

```

 $\wedge$  value  $\in$  [ CORRECT  $\rightarrow$  VALUES ]
 $\wedge$  decision  $\in$  [ ALL  $\rightarrow$  VALUES  $\cup$  { NO_DECISION } ]
 $\wedge$  round  $\in$  [ CORRECT  $\rightarrow$  ROUNDS ]
 $\wedge$  step  $\in$  [ CORRECT  $\rightarrow$  { S1, S2, S3 } ]
 $\wedge$   $\exists$  A1  $\in$  SUBSET [ src: ALL, r: ROUNDS, v: VALUES ]:
    msgs1 = [ r  $\in$  ROUNDS  $\mapsto$  { m  $\in$  A1: m.r = r } ]
 $\wedge$   $\exists$  A1D  $\in$  SUBSET [ src: ALL, r: ROUNDS, v: VALUES ],
    A1Q  $\in$  SUBSET [ src: ALL, r: ROUNDS ]:
    msgs2 = [ r  $\in$  ROUNDS  $\mapsto$ 
        { D2(mm.src, r, mm.v): mm  $\in$  { m  $\in$  A1D: m.r = r } }
         $\cup$  { Q2(mm.src, r): mm  $\in$  { m  $\in$  A1Q: m.r = r } }
    ]

```




Realistic example:
Ben-Or's Consensus

[github.com/konnov/apalache-examples]

Fault-tolerant distributed systems

Distributed

logically and geographically

Fault-tolerant

individual machines may crash and even act malicious

Safe and live

e.g., no double spending

every transaction is eventually committed

Properties of Distributed Consensus

A distributed algorithm for N replicas
every replica proposes a value $w \in V$

Termination

every correct replica eventually decides on a value $v \in V$

Agreement

if a replica decides on v , no replica decides on $V \setminus \{v\}$

Validity

if a replica decides on v , the value v was proposed earlier

B — Byzantine Protocol

Process P : Initial value x_P .

step 0: set $r := 1$.

step 1: Send the message $(1, r, x_P)$ to all the processes.

step 2: Wait till messages of type $(1, r, *)$ are received from $N - t$ processes. If more than $(N + t)/2$ messages have the same value v , then send the message $(2, r, v, D)$ to all processes. Else send the message $(2, r, ?)$ to all processes.

step 3: Wait till messages of type $(2, r, *)$ arrive from $N - t$ processes.

(a) If there are at least $t + 1$ D -messages $(2, r, v, D)$, then set $x_P := v$.

(b) If there are more than $(N + t)/2$ D -messages then **decide** v .

(c) Else set $x_P = 1$ or 0 each with probability $\frac{1}{2}$.

step 4: Set $r := r + 1$ and go to step 1.

$$n > 5 \cdot t \wedge t \geq f$$

Another Advantage of Free Choice:
Completely Asynchronous Agreement Protocols

(Extended Abstract)

Michael Ben-Or [†]

Type definitions

```
1  ----- MODULE typedefs -----
2  EXTENDS Variants
3
4  (*
5   * Type definitions:
6   *
7   * Type-1 messages.
8   * @typeAlias: msgA = { src: REPLICA, r: Int, v: Int };
9   *
10  * Type-2 messages.
11  * @typeAlias: msgB = Q({ src: REPLICA, r: Int }) | D({ src: REPLICA, r: Int, v: Int });
12  *)
13  typedefs_aliases  $\triangleq$  TRUE
14
15  \* predefined constants for the steps
16  S1  $\triangleq$  "S1_OF_STEP"
17  S2  $\triangleq$  "S2_OF_STEP"
18  S3  $\triangleq$  "S3_OF_STEP"
```


Auxiliary type constructors

[typedefs.tla]

```
20 \* @type: (REPLICA, Int, Int) => $msgA;
21 M1(src, round, value)  $\triangleq$  [ src  $\mapsto$  src, r  $\mapsto$  round, v  $\mapsto$  value ]
22
23 \* @type: (REPLICA, Int) => $msgB;
24 Q2(src, round)  $\triangleq$  Variant("Q", [ src  $\mapsto$  src, r  $\mapsto$  round ])
25
26 \* @type: $msgB => Bool;
27 IsQ2(msg)  $\triangleq$  VariantTag(msg) = "Q"
28
29 \* @type: $msgB => { src: REPLICA, r: Int };
30 AsQ2(msg)  $\triangleq$  VariantGetUnsafe("Q", msg)
31
32 \* @type: (REPLICA, Int, Int) => $msgB;
33 D2(src, round, value)  $\triangleq$  Variant("D", [ src  $\mapsto$  src, r  $\mapsto$  round, v  $\mapsto$  value ])
34
35 \* @type: $msgB => Bool;
36 IsD2(msg)  $\triangleq$  VariantTag(msg) = "D"
37
38 \* @type: $msgB => { src: REPLICA, r: Int, v: Int };
39 AsD2(msg)  $\triangleq$  VariantGetUnsafe("D", msg)
```

```
15  \* The set of values to choose from
16  VALUES == { 0, 1 }
17
18  CONSTANTS
19      \* The total number of replicas.
20      \* @type: Int;
21      N,
22      \* An upper bound on the number of faulty replicas.
23      \* @type: Int;
24      T,
25      \* The actual number of faulty replicas (unknown to the replicas).
26      \* @type: Int;
27      F,
28      \* The set of the correct (honest) replicas.
29      \* @type: Set(REPLICA);
30      CORRECT,
31      \* The set of the Byzantine (faulty) replicas.
32      \* @type: Set(REPLICA);
33      FAULTY,
34      \* The set of rounds, which we bound for model checking.
35      \* @type: Set(Int);
36      ROUNDS
37
38  ALL == CORRECT \union FAULTY
39  NO_DECISION == -1
```

45 `∨ VARIABLES`

```
46   \* The current value by a replica, called $x_P$ in the paper.
47   \* @type: REPLICAS -> Int;
48   value,
49   \* The decision by a replica, where -1 means no decision.
50   \* @type: REPLICAS -> Int;
51   decision,
52   \* The round number of a replica, called $r$ in the paper.
53   \* @type: REPLICAS -> Int;
54   round,
55   \* The replica step: S1, S2, S3.
56   \* @type: REPLICAS -> STEP;
57   step,
58   \* Type-1 messages sent by the correct and faulty replicas, mapped by rounds.
59   \* @type: Int -> Set($msgA);
60   msgs1,
61   \* Type-2 messages sent by the correct and faulty replicas, mapped by rounds.
62   \* @type: Int -> Set($msgB);
63   msgs2
```

```

78  ∨ Init ≜
79    \* non-deterministically choose the initial values
80    ∧ value ∈ [ CORRECT → VALUES ]
81    ∧ decision = [ r ∈ CORRECT ↦ NO_DECISION ]
82    ∧ round = [ r ∈ CORRECT ↦ 1 ]
83    ∧ step = [ r ∈ CORRECT ↦ S1 ]
84    ∧ msgs1 = [ r ∈ ROUNDS ↦ {} ]
85    ∧ msgs2 = [ r ∈ ROUNDS ↦ {} ]

```

```

103  \* @type: REPLICA => Bool;
104  Step1(id) ≜
105    LET r ≜ round[id] IN
106    ∧ step[id] = S1
107    \* "send the message (1, r, x_P) to all the processes"
108    ∧ msgs1' = [msgs1 EXCEPT ![r] = @ U { M1(id, r, value[id]) } ]
109    ∧ step' = [step EXCEPT ![id] = S2]
110    ∧ UNCHANGED ( value, decision, round, msgs2 )

```

```

112 Step2(id)  $\triangleq$ 
113   LET r  $\triangleq$  round[id] IN
114    $\wedge$  step[id] = S2
115    $\wedge$   $\exists$  received  $\in$  SUBSET msgs1[r]:
116     \* "wait till messages of type (1, r, *) are received from N - T processes"
117      $\wedge$  Cardinality(Senders1(received))  $\geq$  N - T
118      $\wedge$  LET Weights  $\triangleq$  [ v  $\in$  VALUES  $\mapsto$ 
119       | Cardinality(Senders1({ m  $\in$  received: m.v = v }) ) ]
120       IN
121        $\boxed{v}$   $\exists$  v  $\in$  VALUES:
122         \* "if more than (N + T)/2 messages have the same value v..."
123          $\wedge$  2 * Weights[v] > N + T
124         \* "...then send the message (2, r, v, D) to all processes"
125          $\wedge$  msgs2' = [msgs2 EXCEPT ![r] = @  $\boxed{U}$  { D2(id, r, v) } ]
126        $\vee \wedge \forall$  v  $\in$  VALUES: 2 * Weights[v]  $\leq$  N
127       | \* "Else send the message (2, r, ?) to all processes"
128        $\wedge$  msgs2' = [msgs2 EXCEPT ![r] = @  $\boxed{U}$  { Q2(id, r) } ]
129    $\wedge$  step' = [ step EXCEPT ![id] = S3 ]
130    $\wedge$  UNCHANGED ( value, decision, round, msgs1 )

```



```

132 < Step3(id) ≐
133   LET r ≐ round[id] IN
134   ∧ step[id] = S3
135 < ∧ ∃ received ∈ SUBSET msgs2[r]:
136   \* "Wait till messages of type (2, r, *) arrive from N - T processes"
137   ∧ Cardinality(Senders2(received)) ≥ N - T
138 < ∧ LET Weights ≐ [ v ∈ VALUES ↦
139   |   Cardinality(Senders2({ m ∈ received: IsD2(m) ∧ AsD2(m).v = v }) )
140   |   IN
141 <   [v] ∃ v ∈ VALUES:
142   |   \* "(a) If there are at least T+1 D-messages (2, r, v, D),
143   |   |   \* then set x_P to v"
144   |   |   ∧ Weights[v] ≥ T + 1
145   |   |   ∧ value' = [value EXCEPT ![id] = v]
146   |   |   \* "(b) If there are more than (N + T)/2 D-messages..."
147 < |   |   ∧ IF 2 * Weights[v] > N + T
148   |   |   |   \* "...then decide v"
149   |   |   |   THEN decision' = [decision EXCEPT ![id] = v]
150   |   |   |   ELSE decision' = decision

```

```

151 <   |   |   [v] ∧ ∀ v ∈ VALUES: Weights[v] < T + 1
152 <   |   |   |   ∧ ∃ next_v ∈ VALUES:
153   |   |   |   |   \* "(c) Else set x_P = 1 or 0 each with probability 1/2."
154   |   |   |   |   \* We replace probabilities with non-determinism.
155   |   |   |   |   ∧ value' = [value EXCEPT ![id] = next_v]
156   |   |   |   |   ∧ decision' = decision
157   |   |   |   \* the condition below is to bound the number of rounds for model checking
158   |   |   |   ∧ r + 1 ∈ ROUNDS
159   |   |   |   \* "Set r := r + 1 and go to step 1"
160   |   |   |   ∧ round' = [ round EXCEPT ![id] = r + 1 ]
161   |   |   |   ∧ step' = [ step EXCEPT ![id] = S1 ]
162   |   |   |   ∧ UNCHANGED ( msgs1, msgs2 )

```

```

164 FaultyStep  $\triangleq$ 
165   \* the faulty replicas collectively inject messages for a single round
166    $\wedge \exists r \in \text{ROUNDS}$ :
167      $\wedge \exists F1 \in \text{SUBSET [ src: FAULTY, r: \{ r \}, v: \text{VALUES } ]}$ :
168       msgs1' = [ msgs1 EXCEPT ![r] = @ U F1 ]
169      $\wedge \exists F2D \in \text{SUBSET \{ D2(src, r, v): src \in \text{FAULTY}, v \in \text{VALUES } \}}$ :
170        $\exists F2Q \in \text{SUBSET \{ Q2(src, r): src \in \text{FAULTY } \}}$ :
171         msgs2' = [ msgs2 EXCEPT ![r] = @ U F2D U F2Q ]
172      $\wedge \text{UNCHANGED ( value, decision, round, step )}$ 

```

```

174 CorrectStep  $\triangleq$ 
175    $\exists id \in \text{CORRECT}$ :
176     V Step1(id)
177     V Step2(id)
178     V Step3(id)

```

```

180  $\vee$  Next  $\triangleq$ 
181   V CorrectStep
182   V FaultyStep

```

```

186   \* No two correct replicas decide on different values
187   AgreementInv  $\triangleq$ 
188      $\forall id1, id2 \in \text{CORRECT}$ :
189       V decision[id1] = NO_DECISION
190       V decision[id2] = NO_DECISION
191       V decision[id1] = decision[id2]

```

Model checking instance

```

1 -----
2 EXTENDS Integers, typedefs
3
4 N == 6
5 T == 1
6 F == 1
7 CORRECT == {
8   "0_OF_REPLICA", "1_OF_REPLICA", "2_OF_REPLICA", "3_OF_REPLICA", "4_OF_REPLICA"
9 }
10 FAULTY == {"5_OF_REPLICA"}
11 ROUNDS == 1..3
12 -----
13 VARIABLES
14   /* The current value by a replica, called $x_P$ in the paper.
15   /* @type: REPLICA -> Int;
16   value,
17   /* The decision by a replica, where -1 means no decision.
18   /* @type: REPLICA -> Int;
19   decision,
20   /* The round number of a replica, called $r$ in the paper.
21   /* @type: REPLICA -> Int;
22   round,
23   /* The replica step: S1, S2, S3.
24   /* @type: REPLICA -> STEP;
25   step,
26   /* Type-1 messages sent by the correct and faulty replicas, mapped by rounds.
27   /* @type: Int -> Set($msgA);
28   msg1,
29   /* Type-2 messages sent by the correct and faulty replicas, mapped by rounds.
30   /* @type: Int -> Set($msgB);
31   msg2
32
33 INSTANCE Ben_or83
34 =====

```


Checking “falsy” invariants

```
195  \* An example of a replica that has made a decision
196  ∨ DecisionEx ≜
197  |   ¬(∃ id ∈ CORRECT: decision[id] ≠ NO_DECISION)
198  |
199  \* An example of all correct replicas having made a decision
200  ∨ AllDecisionEx ≜
201  |   ¬(∀ id ∈ CORRECT: decision[id] ≠ NO_DECISION)
```

```
$ apalache-mc check --inv=DecisionEx \  
--init=Init --next=Next MC_n6t1f1.tla
```

26 min 16 sec, 1.2G ❌

```
apalache-mc simulate --length=30 --inv=AllDecisionEx \  
--init=Init --next=Next MC_n6t1f1.tla
```

1 min 9 sec, 1.4G ❌

```
$ apalache-mc check --inv=DecisionEx \  
--init=InitWithFaults --next=CorrectStep MC_n6t1f1.tla
```

39 sec, 1.1G ❌

```
apalache-mc simulate --length=30 --inv=AllDecisionEx \  
--init=InitWithFaults --next=CorrectStep MC_n6t1f1.tla
```

1 min 9 sec, 1.4G ❌

```
apalache-mc check --length=30 --inv=AllDecisionEx \  
--init=InitWithFaults --next=CorrectStep MC_n6t1f1.tla
```

1 hour 55 min, 1.7G ❌

Injecting faults in the initial states

```
87 ∨ InitWithFaults ≐
88   \* non-deterministically choose the initial values
89   ∧ value ∈ [ CORRECT → VALUES ]
90   ∧ decision = [ r ∈ CORRECT ↦ NO_DECISION ]
91   ∧ round = [ r ∈ CORRECT ↦ 1 ]
92   ∧ step = [ r ∈ CORRECT ↦ S1 ]
93   \* non-deterministically initialize the messages with faults
94 ∨ ∧ ∃ F1 ∈ SUBSET [ src: FAULTY, r: ROUNDS, v: VALUES ]:
95     | msgs1 = [ r ∈ ROUNDS ↦ { m ∈ F1: m.r = r } ]
96 ∨ ∧ ∃ F1D ∈ SUBSET [ src: FAULTY, r: ROUNDS, v: VALUES ],
97     | F1Q ∈ SUBSET [ src: FAULTY, r: ROUNDS ]:
98 ∨     | msgs2 = [ r ∈ ROUNDS ↦
99 ∨     |     { D2(mm.src, r, mm.v): mm ∈ { m ∈ F1D: m.r = r } }
100     |     ∪ { Q2(mm.src, r): mm ∈ { m ∈ F1Q: m.r = r } }
101     | ]
```

Main litmus test

Check AgreementInv for $n = 6, f = 2$

It must be **✗**

```
$ seq 0 9 | parallel --delay 1 apalache-mc simulate --out-dir=o/{ } \  
  --length=30 --init=InitWithFaults --next=CorrectStep \  
  --inv=AgreementInv MC_n6t1f2.tla
```

```
State 10: state invariant 0 violated. ✗  
Total time: 17.859 sec
```

```
$ apalache-mc check --length=30 --init=InitWithFaults \  
  --next=CorrectStep --inv=AgreementInv MC_n6t1f2.tla
```

```
State 10: state invariant 0 violated.  
It took me 0 days 0 hours 11 min 39 sec ✗
```

Checking AgreementInv

Check AgreementInv for $n = 6, t = 1, f = 1$

It must be 


```
$ apalache-mc check --length=18 --init=InitWithFaults \  
  --next=CorrectStep --inv=AgreementInv MC_n6t1f1.tla
```

OK in 18h 53 min 

```
$ seq 0 19 | parallel --delay 1 --halt now, fail=1 \  
  apalache-mc simulate -out-dir=s/{ } --length=25 \  
  --init=InitWithFaults --next=CorrectStep --inv=AgreementInv MC_n6t1f1.tla
```

OK in 3h - 3h 20 min 

Cactus Plot



Inductive invariant?

IndInv \triangleq

```
 $\wedge$  Lemma2_NoEquivocation1ByCorrect
 $\wedge$  Lemma3_NoEquivocation2ByCorrect
 $\wedge$  Lemma4_MessagesNotFromFuture
 $\wedge$  Lemma5_RoundNeedsSentMessages
 $\wedge$  Lemma6_DecisionDefinesValue
 $\wedge$  Lemma7_D2RequiresQuorum
 $\wedge$  Lemma8_Q2RequiresNoQuorum
 $\wedge$  Lemma9_RoundsConnection
 $\wedge$  Lemma10_M1RequiresQuorum
 $\wedge$  Lemma11_ValueOnQuorum
 $\wedge$  Lemma12_CannotJumpRoundsWithoutQuorum
 $\wedge$  Lemma13_ValueLock
 $\wedge$  * this lemma is rather slow
 $\wedge$  Lemma1_DecisionRequiresLastQuorum
```

TypeOK \triangleq

```
 $\wedge$  value  $\in$  [ CORRECT  $\rightarrow$  VALUES ]
 $\wedge$  decision  $\in$  [ ALL  $\rightarrow$  VALUES  $\cup$  { NO_DECISION } ]
 $\wedge$  round  $\in$  [ CORRECT  $\rightarrow$  ROUNDS ]
 $\wedge$  step  $\in$  [ CORRECT  $\rightarrow$  { S1, S2, S3 } ]
 $\wedge$   $\exists$  A1  $\in$  SUBSET [ src: ALL, r: ROUNDS, v: VALUES ]:
    msgs1 = [ r  $\in$  ROUNDS  $\mapsto$  { m  $\in$  A1: m.r = r } ]
 $\wedge$   $\exists$  A1D  $\in$  SUBSET [ src: ALL, r: ROUNDS, v: VALUES ],
    A1Q  $\in$  SUBSET [ src: ALL, r: ROUNDS ]:
    msgs2 = [ r  $\in$  ROUNDS  $\mapsto$ 
        { D2(mm.src, r, mm.v): mm  $\in$  { m  $\in$  A1D: m.r = r } }
         $\cup$  { Q2(mm.src, r): mm  $\in$  { m  $\in$  A1Q: m.r = r } }
    ]
```

IndInit \triangleq


```
 $\wedge$  TypeOK
 $\wedge$  IndInv
```

[Ben_or83_inductive.tla]

Performance: $n = 6, f = 1$

- 13 lemmas, about 13h of my time
- dozens of attempts
- up to 20 model checker runs each
- **Challenge:** fix the lemmas by looking at the counterexamples
- not trying to write a proof on paper

1. $Init \Rightarrow IndInv$: 13 sec
2. $IndInit \Rightarrow AgreementInv$: 21 min
3. $IndInit \wedge Next \Rightarrow IndInv$



Fineprint

We have proven *AgreementInv* by induction for:

- 5 correct and 1 faulty replica
- 3 rounds

It's not a parameterized proof!

Sufficient in practice?



Heavy-weight verification

- Complete functional verification
- Hoare-style proofs

Mid-weight verification

- Complete model checking
- Conformance testing



Lightweight verification

- Static analysis
- Property-based testing

- **Model checking**
- **Stateless exploration**
- **Bug finding**

Conclusions

Directions

- Make “simulate” learn about good/bad executions – fuzzing
- Introduce a less explosive encoding, e.g., Alloy’s?
- Better support for parallel runs

- There is no company to dictate a roadmap, it’s truly open source



Jure Kukovec



Thanh-Hai Tran



Marijana Lazić



Josef Widder



Jure Kukovec



Shon Feder



Gabriela Moreira
@bugarela



Igor Konnov
@konnov



Thomas Pani



Andrey Kupriyanov



Philip Offtermatt



Rodrigo Otoni



INTERCHAIN



[github.com/apalache-mc/apalache]



APALACHE

A symbolic model checker for TLA+

build passing

Apalache translates [TLA+](#) into the logic supported by SMT solvers such as [M](#) inductive invariants (for fixed or bounded parameters) and check safety of b... (checking). To see the list of supported TLA+ constructs, check the [supporte](#) under the same assumptions as [TLC](#). However, Apalache benefits from cons... potentially larger state-spaces, e.g., involving integer clocks and Byzantine f...

To learn more about TLA+, visit [Leslie Lamport's page on TLA+](#) and his [Vide](#)

Releases

Check the [releases page](#) for our latest release.

For a stable release, we recommend that you pull the latest docker image with `docker pull ghcr.io/apalache-mc/apalache:main`, use the jar from the most recent release, or checkout the source code from the most recent release tag.

To try the latest cool features, check out the head of the [main branch](#).

[apalache.discourse.group]

← → ↻ 🔒 https://apalache.discourse.group ☆ 🗄️ 👤 🔍

☰ APALACHE

Sign Up Log In

categories ▾ tags ▾ Latest Hot Categories

Topic Replies Activity

🚩 Welcome to Apalache: symbolic model checker for TLA+ and Quint! 🤖

■ General

We are so glad you joined us. Apalache: symbolic model checker for TLA+ and Quint The place to ask questions and discuss applications and research Here are some things you can do to get started: 🗣️ Intr... read more

Example: trying to run `apalache-mc check` on `CoffeeCan.tla`

■ Apalache Questions